FAST **250**PUMP PRO PLUS



Powerful and fast fogging system, can cover up to **750 m³ in 30 seconds** (250 m³ visibility less than 1 m).





GENERAL SPECIFICATIONS

Weight of the fogging machine	about 14 KG	
Weight with packaging	about 15 KG	
Units on one pallet 100×120	24	
Dimension of the machine	21,5 X27,0 XH43,5	
Dimension of the packaging	26,0 X38,0 XH53,0	
Colors	white	
Working time without mains power	about 2 hours	
Heating time from cold	about 50 minutes	
Vertical mounting	yes	
Horizontal mounting	yes	
Usb port for monitoring	yes	
Nozzle tamper	yes	
Serial interface RS232 with UR FOG Standard protocol	yes	
Alarm kit	opzional	

FOGGING SYSTEM

New heating system "Layer"	yes	
Coverage in a single shot (visibility more than 1,5 m)	up to 750 m³	
Coverage in a single shot (visibility less than 1 m)	up to 250 m³	
Max seconds of fog emission	30 sec	
Max fog emitted with full fog bag	1300 m³	
Number of bag	1	
Fog tank capacity	1 x 1000 ml	
Shooting specification	programmable in seconds	
Bag included	1	

STANDARD

Complies with european CE	yes
Fog fluid is certified	yes
Meets european standard	yes

ELECTRICAL SPECIFICATIONS

Mains power	230 V or 120 V	
Average power consumption	37 W	
Back up battery (not included)	yes	
Pir sensor validation input	yes	
Shot confirmation output	yes	
Power supply	yes	

It is a powerful and fast fogging system, ideal to protect small and medium areas like shops, homes, banks and generally all professional applications where a top security technology is needed.

It is prearranged to an easy wall installation and it has a side compartment to equip boards or accessories if needed.



Accessories and refills FAST 250 PUMP PRO PLUS

CODE	ACCESSORIES AND REFILLS	FAST 250 PUMP PRO PLUS
FFLXRC10	Fluid bag 1000 ml	
FFLXRC10FG	Fluid bag 1000 ml Food Grade	
FFLXRC33	Fluid bag 3000 ml	(Top box)
FFLXRC33FG	Fluid bag 3000 ml Food Grade	(Top box)
FFLXTP30	Top box fluid 3L Pump 250-500	
F23PRUG7	Nozzle extension 7 cm	
F1M03UG3	3 holes nozzle	
F23KITD	Demo Kit (key + keyfob/receiver + button)	
F23KITA	Anti-robbery Kit: cable + jumper	
URRE	Relay board	
F123KEY	Arming key	
F23STHPRO	Wall bracket Pump 250-500	
URTR	Keyfob + riceiver	
URT	Additional keyfob	
URRS232	Transceiver rs232 5/12 V	
URCLWF	Active Cloud Lan / WIFI board	
URCLWFA	Wifi antenna module	
URCLWFPP	Mounting kit Pro Plus (flat cable Pro Plus + 3 x 20 mm spacers)	



Adjustable

nozzle

function

with



Active Cloud LAN / Wifi board

The WIFI LAN board allows wired or wireless Lan connection. Through the extremely secure Cloud service, provided for free, it allows, in addition to system monitoring, to remotely arm, shoot and set shooting time of the fogging system.





Pro Plus board



Optional 2Ah battery

to power the electronic board and motors in case of mains power failure

Power supply for the electronic board and motors



Exclusive patented system that allows to detect automatically if the nozzle has been obstructed by sending a signal in case of tampering.



Disposable recharge, very easy to replace, at a very competitive price.



Thanks to the massive insulation UR FOG fogging systems have a very low power consumption and can shoot for a long time in absence of mains power; temperature remains stable over time.

Long lasting operation time without mains The innovative thermal insulation

of the heater allows UR Fog systems to work for a long period of time without mains power: about 2 hours!



Shooting

RS232


FOG STORM PUMP Specially designed

to work with high-glycol

percentage fluids

A unique serial bus to plug on the electronic board an add on card that allows to interface easily the machine with alarms and to control the fogging system even from remote locations. A standard protocol is available for all machines.

Electronic board



INPUTS

+12V power input GND power input ARM Arming input SHOOT Shooting input **GND**

OUTPUTS

EMPTY Empty cylinder output **FAULT** Fault output TAMPER Tamper output

CONFIRM Shot confirmation output

PIR SENSOR VALIDATION INPUT

P+ +12V for PIR power supply

P-GND for PIR power supply / COM. PIR

DV

